Technical data sheet

Cable routing trunking, type LKM 20030

Item no. 6248470

Duct cover and base with base perforation. Equipotential bonding is guaranteed between the cover and the base without any additional aids. The LKM cable routing duct, type LKM 20030FS, has been tested for the maintenance of electrical function as a routing system according to DIN 4102 Part 12. Please note the cable types tested in the BSS fire protection systems division!

St	Steel
FSK	Strip galvanised/powder-coated

Master data

Item no.	6248470
Type	LKM20030RW
Description 1	Cable trunking
Description 2	with base perforation
Dimension	20x30x2000
Colour	Pure white
RAL number	9010
Material	Steel
Material symbol	St
Surface	Strip galvanised/powder-coated
Surface to DIN	DIN EN 10346
Surface symbol	FSK
Smallest sales unit (VG)	2,00 m
Weight	58,00 kg/100 m

Technical data sheet

Cable routing trunking, type LKM 20030

Item no. 6248470

Technical data



Length	2.000,00 mm
Width	30,00 mm
Height	24,00 mm
lampDimension WxH	30 x 24 mm
Number of fixed partitions	0,00
Number of insertable partitions	1,00
Cover version	Loose
Fastening type	Base perforation
Halogen-free	☑
Cable retaining clip	☐
Duct connector	☐
Usable cross-section	519,00 cm²
Protective film	☐