Technical data sheet

Device installation trunking, type GAA90170

Item no. 6279500

Device installation trunking Without base perforation for direct wall mounting or mounting on panels. Over-lengths up to 6,000 mm for trunking bases and covers as well as other RAL colours can be provided on request. The visible surfaces of the painted device installation trunking are laminated.

Alu Aluminium

Additional product text, instruction	The cover must be ordered separately. We recommend the use of the trunking clamp.
Additional product text 1	Note: For anodised device installation trunking and fittings made from aluminium, light colour differences caused by tolerance based on the material and process conditions, cannot be avoided (according to DIN 17 611). Alternatively, we recommend powder coating in the colour RAL 9006 (white aluminium).

Master data

Item no.	6279500
Type	GA-A90170RW
Description 1	Device installation trunking
Description 2	asymmetrical
Dimension	90x170x2000
Colour	Pure white
RAL number	9010
Material	Aluminium
Material symbol	Alu
Smallest sales unit (VG)	2,00 m
Weight	284,50 kg/100 m

Technical data sheet

Device installation trunking, type GAA90170

Item no. 6279500

Technical data



Length	2.000,00 mm
Width	170,00 mm
Height	90,00 mm
Number of covers	1,00
Number of insertable partitions	1,00
Rear panel version (inner side)	Continuous C profile
Rectangular shape	☑
Base perforation	Without base perforation
Halogen-free	☑
Cable retaining clip	☐
Duct depth	90,00 mm
Trunking height	170,00 mm
Duct connector	☐
Cover mounting type	Internal
Mounting perforation in base	☐
Usable cross-section	11.756,00 mm²
Cover width	76,5 mm
Cover width 2	0,00 mm
Cover width 3	0,00 mm
Cover supplied	☐
Protective film	☑
Symmetrical	☑