Technical data sheet

Device installation trunking, type GA-A70170

Item no. 6279403

Device installation trunking Without base perforation for direct wall mounting or mounting on panels. Over-lengths up to 6,000 mm for trunking bases and covers as well as other RAL colours can be provided on request. The visible surfaces of the painted device installation trunking are laminated.

Alu	Aluminium
EL	Anodised

Additional product text, instruction	The cover must be ordered separately. We recommend the use of the trunking clamp.
Additional product text 1	Note: For anodised device installation trunking and fittings made from aluminium, light colour differences caused by tolerance based on the material and process conditions, cannot be avoided (according to DIN 17 611). Alternatively, we recommend powder coating in the colour RAL 9006 (white aluminium).

Master data

Item no.	6279403
Type	GA-A70170EL
Description 1	Device installation trunking
Description 2	asymmetrical
Dimension	70x170x2000
Material	Aluminium
Material symbol	Alu
Surface	Anodised
Surface symbol	EL
Smallest sales unit (VG)	2,00 m
Weight	262,90 kg/100 m

Technical data sheet

Device installation trunking, type GA-A70170

Item no. 6279403

Technical data



Length	2.000,00 mm
Width	170,00 mm
Height	70,00 mm
Number of covers	1,00
Number of insertable partitions	1,00
Rear panel version (inner side)	Continuous C profile
Rectangular shape	☑
Base perforation	Without base perforation
Halogen-free	☑
Cable retaining clip	☐
Duct depth	70,00 mm
Trunking height	170,00 mm
Duct connector	☐
Cover mounting type	Internal
Mounting perforation in base	☐
Usable cross-section	8.620,00 mm²
Cover width	76,5 mm
Cover width 2	0,00 mm
Cover width 3	0,00 mm
Cover supplied	☐
Protective film	☑
Symmetrical	☐